×



https://www.eibabo.com/en/rzb/led-outdoor-spotlight-56w-98gr-downlight-spot-floodlight-1x37w-72171 6.114.1-eb13211267



LED outdoor spotlight 56W 98Gr - Downlight/spot/floodlight 1x37W 721716.114.1

ownlight/spot/floodlight 1x37W 721716.114.1

RZB

721716.114.1 4051859012153 EAN/GTIN

245,09 USD excl. VAT**

plus **shipping**



4-5 days* (USA)

LED outdoor spotlight 4000K 98Gr 721716.114.1 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for pedestal/floor mounting, Adjustability not adjustable, Light source LED not replaceable, With light source, Suitable for number of light sources 1, Socket without, Housing material aluminium, Surface powder-coated, housing color silver, cover material transparent glass, type of voltage AC, nominal voltage 220 ... 240V, control gear LED control gear, current-controlled, with control gear, without dimming function, highly specular reflector, light distributor reflector, light distributor reflector, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct, rated service life L80/B10 at 25 °C 50000h, degree of protection (IP) IP65, degree of protection (NEMA) other, impact resistance IK07, protection class I, rated ambient temperature according to IEC62722-2-1 -25 ... 50°C, suitable for lamp power 37 ... 37W, max. system power 37W, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous flux 4250 ... 4250lm, rated luminous flux according to IEC 62722-2-1 4250lm, lamp luminous efficacy 115lm/W, power factor 0.95, width 142mm, height/depth 336mm, length 267mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connectable conductor cross-section 2.5 ... 2.5mm², connection type plug-in terminal, luminaire with limited surface temperature "D mark", luminous efficacy of luminaire 115lm/W, glow-wire test according to IEC 60695-2-11 960 °C - 30 s, photobiological safety according to EN 62471 RG1, color consistency (McAdam ellipse) SDCM3, Made in Germany. 3 different light distributions: Narrow Spot, Medium Spot and Flood. Stationary installation or mobile with plug and 5 m connecting cable. Seawater resistant coating optionally available. Central battery emergency light option available. Second cable inlet for looping through. Reduced connected load with the same luminous flux of the switchable version to save energy. Control gear on/off. Light color 840. LED service life 50,000 h (L80, B10). Pole and wall mounting accessories available. Suitable for use in the food and beverage industry. Housing made of corrosion-resistant die-cast aluminum for outdoor use, powder-coated. Bracket aluminum powder-coated. Cover clear safety glass (ESG), ceramic coated. COB-LED with interchangeable socket. Reflector of pure aluminum, high-gloss anodised. Standard with diaphragm valve to prevent condensation. With plug-in connection terminal 3x 2.5 mm². Suitable for cable diameters up to d 13 mm. Second cable bushing for network...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

**** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

